

SAFETY DATA SHEET

SICI10008A

Section: 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SICI10008A

Other means of identification : Not applicable.

Recommended use : CORROSION/SCALE INHIBITOR

Restrictions on use : Refer to available product literature or ask your local Sales Representative for restrictions on use and dose limits.

Company : ChampionX LLC
11177 S. Stadium Drive
Sugar Land, Texas 77478
USA
TEL: (281) 632-6500

Emergency telephone number : (800) 424-9300 (24 Hours) CHEMTREC

Issuing date : 08/11/2023

Section: 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 4

Acute toxicity (Dermal) : Category 4

Skin irritation : Category 2

Serious eye damage : Category 1

Skin sensitization : Category 1

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 1 (Eyes)

- single exposure

Specific target organ toxicity : Category 3 (Central Nervous System)

- single exposure

Specific target organ toxicity : Category 2 (Heart, Liver, Kidney)

- repeated exposure

GHS Label element

Hazard pictograms :



Signal Word :
Danger

Hazard Statements :
Flammable liquid and vapour.

SAFETY DATA SHEET

SICI10008A

Harmful if swallowed, in contact with skin or if inhaled.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.
Causes damage to organs (Eyes).
May cause damage to organs (Heart, Liver, Kidney) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
Storage:
Store in a well-ventilated place.
Disposal:
Dispose of contents/ container to an approved waste disposal plant.

Other hazards : None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Concentration: (%)</u>
Methanol	67-56-1	10 - 30
Amine Triphosphate	Proprietary	5 - 10
Sodium Phosphate, Tribasic	7601-54-9	1 - 5
Quaternary ammonium compounds	Proprietary	1 - 5
2-Mercaptoethanol	60-24-2	1 - 5
Quaternary ammonium compound	Proprietary	1 - 5
Ethylene Glycol	107-21-1	1 - 5

Section: 4. FIRST AID MEASURES

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

SAFETY DATA SHEET

SICI10008A

- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention.
- Protection of first-aiders : In event of emergency assess the danger before taking action. Do not put yourself at risk of injury. If in doubt, contact emergency responders. Use personal protective equipment as required.
- Notes to physician : Treat symptomatically.
- Most important symptoms and effects, both acute and delayed : See Section 11 for more detailed information on health effects and symptoms.

Section: 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Foam
Carbon dioxide
Dry powder
Other extinguishing agent suitable for Class B fires
For large fires, use water spray or fog, thoroughly drenching the burning material.
- Unsuitable extinguishing media : None known.
- Specific hazards during firefighting : Fire Hazard
Keep away from heat and sources of ignition.
Flash back possible over considerable distance.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Hazardous combustion products : Decomposition products may include the following materials: Carbon oxides nitrogen oxides (NO_x) Sulphur oxides Oxides of phosphorus Hydrogen chloride
- Special protective equipment for firefighters : Use personal protective equipment.
- Specific extinguishing methods : Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
- Methods and materials for containment and cleaning up : Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise

SAFETY DATA SHEET

SICI10008A

contain material to ensure runoff does not reach a waterway. Flush away traces with water.

Section: 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid contact with skin and eyes. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Do not ingest. Keep away from fire, sparks and heated surfaces. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Wash hands thoroughly after handling. Use only with adequate ventilation.
- Conditions for safe storage : Keep away from heat and sources of ignition. Keep in a cool, well-ventilated place. Keep away from oxidizing agents. Keep out of reach of children. Keep container tightly closed. Store in suitable labelled containers.
- Suitable material : The following compatibility data is suggested based on similar product data and/or industry experience: Compatibility with Plastic Materials can vary; we therefore recommend that compatibility is tested prior to use.
- Unsuitable material : not determined

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m3	NIOSH REL
		STEL	250 ppm 325 mg/m3	NIOSH REL
		TWA	200 ppm 260 mg/m3	OSHA Z1
Sodium Phosphate, Tribasic	7601-54-9	STEL	5 mg/m3	AIHA WEEL
2-Mercaptoethanol	60-24-2	TWA	0.2 ppm	AIHA WEEL
Ethylene Glycol	107-21-1	TWA (Vapour.)	25 ppm	ACGIH
		STEL (Vapour.)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH

- Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Personal protective equipment

- Eye protection : Safety goggles
Face-shield
- Hand protection : Wear impervious chemical-resistant gloves when handling this product.

SAFETY DATA SHEET

SICI10008A

The following glove types are recommended based on our review of glove manufacturer information and/or other available sources.

Impervious gloves, resistant to chemicals.

butyl-rubber

Other glove types may be used for short term, incidental contact if determined by testing to provide adequate worker protection.

Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection : Wear suitable protective clothing.

Respiratory protection : Use local exhaust ventilation or other engineering controls as necessary to control airborne mist and vapor.
Where concentrations in air may exceed the limits given in this section or when significant vapors or mists are generated, an approved air purifying respirator equipped with suitable filter cartridges is recommended.
Multi-purpose combination filter:
Combined particulates, inorganic and acidic gas/vapour, ammonia/amines and organic vapour type

In event of emergency or planned entry into unknown concentrations, a positive pressure, full-facepiece SCBA or supplied-air respirator should be used.

If respiratory protection is required, institute a complete respiratory protection program including selection, fit testing, training, maintenance and inspection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

The Personal Protective Equipment (PPE) recommendations provided above have been made in good faith based on typical expected conditions of use. PPE selection should always be completed in conjunction with a proper risk assessment and in accordance with a PPE management program.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid
Colour : clear
Odour : Pungent
Flash point : 31.0 °C
pH : no data available
Odour Threshold : no data available
Melting point/freezing point : no data available
Initial boiling point and boiling range : no data available
Evaporation rate : no data available
Flammability (solid, gas) : Not applicable.
Upper explosion limit : no data available
Lower explosion limit : no data available

SAFETY DATA SHEET

SICI10008A

Vapour pressure	: 73.9 mm Hg,
Relative vapour density	: no data available
Relative density	: 1.05, (15.5 °C),
Density	: 8.7 lb/gal
Water solubility	: completely soluble
Solubility in other solvents	: no data available
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: no data available
Thermal decomposition	: no data available
Viscosity, dynamic	: 15.8 mPa.s (-12.2 °C) 3.7 mPa.s (25 °C) 7.3 mPa.s (4.4 °C)
Viscosity, kinematic	: no data available
Molecular weight	: no data available
VOC	: no data available

Note: properties listed in this section may be typical, calculated, or estimated values and should not be used as product specifications or for system design. For product specifications see the COA or Technical Data sheet.

Section: 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as: Carbon oxides nitrogen oxides (NO _x) Sulphur oxides Oxides of phosphorus Hydrogen chloride

Section: 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Potential Health Effects

SAFETY DATA SHEET

SICI10008A

Eyes	: Causes serious eye damage.
Skin	: May cause allergic skin reaction. Toxic in contact with skin. Harmful in contact with skin. Causes skin irritation. May cause allergic skin reaction.
Ingestion	: Toxic if swallowed. May cause blindness if swallowed. May cause blindness if swallowed. Harmful if swallowed.
Inhalation	: Toxic if inhaled. Inhalation may cause central nervous system effects. Causes headache, drowsiness or other effects to the central nervous system. Harmful if inhaled. Inhalation may cause central nervous system effects.
Chronic Exposure	: Suspected of damaging fertility or the unborn child. May cause damage to organs. May cause damage to organs through prolonged or repeated exposure.

Experience with human exposure

Eye contact	: Redness, Pain, Corrosion
Skin contact	: Redness, Irritation, Allergic reactions
Ingestion	: No information available.
Inhalation	: Dizziness, Drowsiness

Toxicity

Product

Acute oral toxicity	: Acute toxicity estimate: 421.18 mg/kg
Acute inhalation toxicity	: Acute toxicity estimate: 12.28 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	: Acute toxicity estimate: 1,151 mg/kg
Skin corrosion/irritation	: no data available
Serious eye damage/eye irritation	: no data available
Respiratory or skin sensitization	: no data available
Carcinogenicity	: no data available
Reproductive effects	: no data available
Germ cell mutagenicity	: no data available
Teratogenicity	: no data available
STOT - single exposure	: no data available
STOT - repeated exposure	: no data available
Aspiration toxicity	: no data available

SAFETY DATA SHEET

SICI10008A

Section: 12. ECOLOGICAL INFORMATION

Toxicity

Environmental Effects : Very toxic to aquatic life.
Harmful to aquatic life with long lasting effects.

Components

Toxicity to fish : Methanol
LC50: 15,400 mg/l
Exposure time: 96 h

Sodium Phosphate, Tribasic
LC50 Oncorhynchus mykiss (rainbow trout): > 100 mg/l
Exposure time: 96 h
Test substance: Information given is based on data obtained from similar substances.

2-Mercaptoethanol
LC50 Leuciscus idus (Golden orfe): 37 mg/l
Exposure time: 96 h

Ethylene Glycol
LC50: 72,860 mg/l
Exposure time: 96 h

Components

Toxicity to daphnia and other aquatic invertebrates : Methanol
EC50 : > 10,000 mg/l
Exposure time: 48 h

Sodium Phosphate, Tribasic
EC50 Daphnia magna (Water flea): > 100 mg/l
Exposure time: 48 h
Test substance: Information given is based on data obtained from similar substances.

2-Mercaptoethanol
EC50 Daphnia magna (Water flea): 0.4 mg/l
Exposure time: 48 h

Quaternary ammonium compound
EC50 : 0.0058 mg/l
Exposure time: 48 h

Ethylene Glycol
EC50 : > 100 mg/l
Exposure time: 48 h

Components

Toxicity to algae : Methanol
EC50 : 22,000 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

SICI10008A

Amine Triphosphate

EC50 : 550 mg/l

Exposure time: 72 h

Sodium Phosphate, Tribasic

EC50 *Desmodesmus subspicatus* (green algae): > 100 mg/l

Exposure time: 72 h

Test substance: Information given is based on data obtained from similar substances.

2-Mercaptoethanol

EC50 *Desmodesmus subspicatus* (*Scenedesmus subspicatus*): 19 mg/l

Exposure time: 72 h

Ethylene Glycol

EC50 : 6,500 mg/l

Exposure time: 96 h

Components

Toxicity to bacteria : Methanol
> 1,000 mg/l

Ethylene Glycol
> 1,995 mg/l

Components

Toxicity to fish (Chronic toxicity) : Methanol
NOEC: 7,900 mg/l
Exposure time: 8.3 d

Ethylene Glycol
NOEC: 15,380 mg/l
Exposure time: 7 d

Components

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : 2-Mercaptoethanol
NOEC: 0.063 mg/l
Exposure time: 21 d
Species: *Daphnia magna* (Water flea)

Ethylene Glycol
NOEC: 8,590 mg/l
Exposure time: 7 d

Persistence and degradability

The organic portion of this preparation is expected to be readily biodegradable.

Mobility

The environmental fate was estimated using a level III fugacity model embedded in the EPI (estimation program interface) Suite TM, provided by the US EPA. The model assumes a steady state condition between the total input

SAFETY DATA SHEET

SICI10008A

and output. The level III model does not require equilibrium between the defined media. The information provided is intended to give the user a general estimate of the environmental fate of this product under the defined conditions of the models.

If released into the environment this material is expected to distribute to the air, water and soil/sediment in the approximate respective percentages;

Air	: <5%
Water	: 30 - 50%
Soil	: 50 - 70%

The portion in water is expected to be soluble or dispersible.

Bioaccumulative potential

This preparation or material is not expected to bioaccumulate.

Other information

no data available

Section: 13. DISPOSAL CONSIDERATIONS

The information presented only applies to the material as supplied. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated at the time of disposal to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Disposal methods	: The product should not be allowed to enter drains, water courses or the soil. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.
------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Disposal considerations	: Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.
-------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

The presence of an RQ component (Reportable Quantity for U.S. DOT) in this product causes it to be regulated with an additional description of RQ for road, or as Environmentally hazardous for road and air, ONLY when the net weight in the package exceeds the calculated RQ for the product.

Land transport (DOT)

Proper shipping name	: FLAMMABLE LIQUID, N.O.S.
Technical name(s)	: Methanol
UN/ID No.	: UN 1993
Transport hazard class(es)	: 3
Packing group	: III
Reportable Quantity (per package)	: 25,000 lbs
RQ Component	: Methanol

SAFETY DATA SHEET

SICI10008A

Air transport (IATA)

Proper shipping name : FLAMMABLE LIQUID, N.O.S.
Technical name(s) : Methanol
UN/ID No. : UN 1993
Transport hazard class(es) : 3
Packing group : III
Reportable Quantity (per package) : 25,000 lbs
RQ Component : Methanol

Sea transport (IMDG/IMO)

Proper shipping name : FLAMMABLE LIQUID, N.O.S.
Technical name(s) : Methanol
UN/ID No. : UN 1993
Transport hazard class(es) : 3
Packing group : III

*Marine pollutant : Quaternary ammonium compounds

* Note: This product is regulated as a Marine Pollutant when shipped by Rail or Highway (in bulk quantities), and when shipped by water in all quantities.

Section: 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Methanol	67-56-1	5000	25000

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Acute toxicity (any route of exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation
Respiratory or skin sensitisation
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.


SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

SAFETY DATA SHEET

SICI10008A

<u>Components</u>	<u>CAS-No.</u>	<u>Weight percent</u>
Methanol	67-56-1	10 - 30 %
Ethylene Glycol	107-21-1	1 - 5 %

California Prop. 65

 **WARNING:** Reproductive Harm - www.P65Warnings.ca.gov

Methanol	67-56-1
Ethylene Glycol	107-21-1

INTERNATIONAL CHEMICAL CONTROL LAWS :

United States TSCA Inventory

On or in compliance with the active portion of the TSCA inventory.

Australia. Australian Industrial Chemicals Introduction Scheme (AICIS)

All substances in this product comply with the Australian Industrial Chemicals Introduction Scheme (AICIS)

Canadian Domestic Substances List (DSL)

The substances in this preparation are listed on the Domestic Substances List (DSL), are exempt, or have been reported in accordance with the New Substances Notification Regulations.

Japan. ENCS - Existing and New Chemical Substances Inventory

On the inventory, or in compliance with the inventory

Korea. Korean Existing Chemicals Inventory (KECI)

On the inventory, or in compliance with the inventory

Philippines Inventory of Chemicals and Chemical Substances (PICCS)

On the inventory, or in compliance with the inventory

China Inventory of Existing Chemical Substances


On the inventory, or in compliance with the inventory

Taiwan Chemical Substance Inventory

not determined

Section: 16. OTHER INFORMATION

NFPA:



0 = not significant
1 = Slight
2 = Moderate
3 = High
4 = Extreme

Revision Date : 08/11/2023

SAFETY DATA SHEET

SICI10008A

Version Number : 1.6
Prepared By : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.