

### **SAFETY DATA SHEET**

### WCI A181 - Corrosion Inhibitor

## **Section 1. Identification**

GHS product identifier : WCI A181 - Corrosion Inhibitor

Other means of identification

: Not available.

Product use : Corrosion inhibitor.

Product type : Liquid.

Manufacturer : Jacam Manufacturing 2013, L.L.C.

P.O.Box 208, 1656 Ave. Q. Sterling, Kansas 67579

Validation date : 3/29/2018

For Chemical Emergency
Spill, Leak Fire, Exposure or

Accident:

: Call CHEMTREC Day or Night

Within USA and Canada 800-424-9300 Or +1 703-527-3887 (Collect calls accepted)

Direct all other calls to:

Jacam Chemicals 2013, L.L.C. 620-278-3355

Mon - Fri 8 a.m. to 5 p.m. (Closed on major holidays)

**Supplier's details** : Jacam Chemicals 2013, L.L.C.

P.O. Box 96, 205 S. Broadway

Sterling, Kansas 67579

### Section 2. Hazards identification

Classification of the substance or mixture

: FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (oral) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

TOXIC TO REPRODUCTION (Unborn child) - Category 1B

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (optic nerve) -

Category 1

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic

Date of issue/Date of revision 3/29/2018 People + Products 

→ Performance™ Version : 1.04

WCI A181 - Corrosion Inhibitor Page: 2/19

### Section 2. Hazards identification

effects) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (thyroid) -Category 1

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 2.7%

### **GHS** label elements

**Hazard pictograms** 







Signal word

Danger

**Hazard statements** : H226 - Flammable liquid and vapor.

H302 - Harmful if swallowed.

H319 - Causes serious eve irritation.

H315 - Causes skin irritation.

H360 - May damage the unborn child.

H370 - Causes damage to organs. (optic nerve) H336 - May cause drowsiness or dizziness.

H372 - Causes damage to organs through prolonged or repeated exposure.

(thyroid)

### **Precautionary statements**

**General** 

: P103 - Read label before use.

P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

**Prevention** 

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves. Wear eye or face protection. Wear protective

clothing.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P241 - Use explosion-proof electrical, ventilating, lighting and all material-

handling equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P233 - Keep container tightly closed.

P271 - Use only outdoors or in a well-ventilated area.

P260 - Do not breathe vapor.

P270 - Do not eat, drink or smoke when using this product.

P264 - Wash hands thoroughly after handling.

: P314 - Obtain medical attention if you feel unwell. Response

P307 + P311 - IF exposed: Call a POISON CENTER or physician.

P304 + P340 + P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel

unwell.

3/29/2018

P301 + P312 + P330 - IF SWALLOWED: Call a POISON CENTER or physician

if you feel unwell. Rinse mouth.

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all

contaminated clothing. Rinse skin with water or shower.

P302 + P352 + P362+P364 - IF ON SKIN: Wash with plenty of soap and water.

Take off contaminated clothing and wash it before reuse.

P332 + P313 - If skin irritation occurs: Obtain medical attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

WCI A181 - Corrosion Inhibitor Page: 3/19

### Section 2. Hazards identification

P337 + P313 - If eye irritation persists: Obtain medical attention.

Storage: P405 - Store locked up.

P403 - Store in a well-ventilated place.

P235 - Keep cool.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

**Hazards not otherwise** 

classified

: None known.

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

INGESTION: Although not a normal route of entry, ingestion is expected to be harmful. DO NOT TAKE INTERNALLY. FOR INDUSTRIAL USE ONLY.

Target organs : Contains material which may cause damage to the following organs: the

reproductive system, gastrointestinal tract, upper respiratory tract, skin, central

nervous system (CNS), eye, lens or cornea, pituitary gland, thyroid.

## Section 3. Composition/information on ingredients

Substance/mixture :

Other means of identification

: Mixture : Not available.

### **CAS** number/other identifiers

**CAS number** : Not applicable.

Ingredient name	%	CAS number
Methanol	10 - 30	67-56-1
Proprietary	1 - 5	Proprietary
Proprietary	1 - 5	Proprietary
Proprietary	1 - 5	Proprietary

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

### **Description of necessary first aid measures**

**Eye contact** 

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 15 minutes. If irritation persists, obtain medical attention. If necessary, call a poison center or physician.

WCI A181 - Corrosion Inhibitor Page: 4/19

### Section 4. First aid measures

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If irritation persists, obtain medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 15 minutes. If irritation persists, obtain medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. If irritation persists, obtain medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness.

**Skin contact** : Causes skin irritation.

Ingestion : Harmful if swallowed. Can cause central nervous system (CNS) depression.

### **Over-exposure signs/symptoms**

**Eye contact**: Adverse symptoms may include the following:

pain or irritation watering redness

**Inhalation** : Adverse symptoms may include the following:

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

Date of issue/Date of revision

3/29/2018

People + Products 

→ Performance\*\*

Version

: 1.04

WCI A181 - Corrosion Inhibitor Page: 5/19

### Section 4. First aid measures

Ingestion

: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths

skeletal malformations

Specific target organ toxicity (single exposure)			
Name	Category	Route of exposure	Target organs
Methanol	Category 1 Category 3	Oral Not applicable.	optic nerve Narcotic effects
Specific target organ toxicity (repeated exposure)			
Name	Category	Route of exposure	Target organs
Proprietary	Category 1	Not determined	thyroid
Aspiration hazard Name		Result	
Not available.			

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

**Protection of first-aiders** 

: No specific treatment.

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing

media

: Use dry chemical, CO2, water spray (fog) or foam.

**Unsuitable extinguishing** 

media

: Do not use water jet.

Specific hazards arising from the chemical

: Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

**Additional Vapor Statement :** 

: Not available. Not available.

People + Products ⇒ Performance™ Version

: 1.04

WCI A181 - Corrosion Inhibitor Page: 6/19

## Section 5. Fire-fighting measures

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon dioxide

carbon monoxide nitrogen oxides sulfur oxides phosphorus oxides halogenated compounds

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

WCI A181 - Corrosion Inhibitor Page: 7/19

## Section 7. Handling and storage

### **Precautions for safe handling**

### **Protective measures**

Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

## Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, including any incompatibilities

Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### **Control parameters**

**Occupational exposure limits** 

Ingredient name	Exposure limits
Methanol	ACGIH TLV (United States, 4/2014).
	Absorbed through skin.
	TWA: 200 ppm 8 hours.
	TWA: 262 mg/m³ 8 hours.
	STEL: 250 ppm 15 minutes.
	STEL: 328 mg/m³ 15 minutes.
	OSHA PEL 1989 (United States, 3/1989).
	Absorbed through skin.
	TWA: 200 ppm 8 hours.
	TWA: 260 mg/m <sup>3</sup> 8 hours.
	STEL: 250 ppm 15 minutes.
	STEL: 325 mg/m³ 15 minutes.
	NIOSH REL (United States, 10/2013).
	Absorbed through skin.
	TWA: 200 ppm 10 hours.
	TWA: 260 mg/m³ 10 hours.
	STEL: 250 ppm 15 minutes.
	STEL: 325 mg/m³ 15 minutes.
	OSHA PEL (United States, 2/2013).
	TWA: 200 ppm 8 hours.
	TWA: 260 mg/m³ 8 hours.

3/29/2018

WCI A181 - Corrosion Inhibitor Page: 8/19

## Section 8. Exposure controls/personal protection

## Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

## **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **Individual protection measures**

### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles

## Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

### **Body protection**

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### **Respiratory protection**

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Personal protective equipment (Pictograms)



WCI A181 - Corrosion Inhibitor Page: 9/19

## Section 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid. [Clear.]

Color : Pale straw colored

Odor : Alcohol-like.
Odor threshold : Not available.

**pH** : 5 to 7

**Melting point** : <-23.333°C (<-10°F)

Boiling point : Not available.

Flash point : Closed cup: 23.889°C (75°F) [Pensky-Martens.]

Evaporation rate : Not available.

Flammability (solid, gas) : Not available.

Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available.

Vapor density : >1 [Air = 1]

Relative density : 0.92 to 0.96

**Density** : 7.67 to 8.02 (lbs/gal)

**Solubility** : Easily soluble in the following materials: cold water.

Partition coefficient: n-octanol/ : Not available.

water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Not available.

## Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not

allow vapor to accumulate in low or confined areas.

**Incompatible materials**: Reactive or incompatible with the following materials:

oxidizing materials

**Hazardous decomposition** 

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

WCI A181 - Corrosion Inhibitor Page: 10/19

## Section 11. Toxicological information

Information on toxicologic	cal effects					
Acute toxicity						
Product/ingredient name	Result		Speci	es	Dose	Exposure
Methanol	LC50 Inhalati		Rat		145000 ppm	1 hours
	LC50 Inhalati		Rat		64000 ppm	4 hours
	LC50 Inhalati		Rat		10 mg/l	4 hours
	LD50 Derma		Rabbi	t	1000 mg/kg	-
	LD50 Oral		Rat		300 mg/kg	-
Proprietary	LD50 Oral		Rat		1832 mg/kg	-
Proprietary	LD50 Derma		Rat		2001 mg/kg	-
<b>-</b>	LD50 Oral		Rat		1310 mg/kg	-
Proprietary	LD50 Dermal		Rabbi	t	2000 mg/kg	-
	LD50 Dermal LD50 Oral	l	Rat Rat		300 mg/kg	-
	LD50 Oral		Rai		84 mg/kg	-
rritation/Corrosion						
Product/ingredient name	Result		Species	Score	Exposure	Observation
Methanol	Eyes - Mode	rate irritant	Rabbit	-	24 hours 1	00 -
	Even Made	and a level and	Dabbit		milligrams	
	Eyes - Moder		Rabbit	-	40 milligra	
	Skin - Moder	ate imiant	Rabbit	-	24 hours 2	
Proprietary	Eyes - Mild ir	ritant	Rabbit	_	milligrams 24 hours 5	
Froprietary	Eyes - Milla II	IIIaIII	Nabbit	-	milligrams	
Proprietary	Eyes - Corne	a onacity	Rabbit	3	3 minutes	14 days
Гюрпетагу	Skin - Visible		Rabbit	-	3 minutes	14 days
Proprietary	Skin - Severe		Rabbit	_	500	14 days
Торпетагу	OKIII - Gevere	5 IIIIICAIII	Rabbit	_	milligrams	_
	Skin - Visible	necrosis	Rabbit	_	3 minutes	4 hours
	Eyes - Redne		Rabbit	2	-	4 hours
	conjunctivae		. 10.001	_		
Sensitization						
	Davida of	0	_		Deculé	
Product/ingredient name	Route of exposure	Specie	<b>9</b> 5		Result	
Proprietary	skin	Guine	a pig		Not sensitizing	
Mutagenicity						
Product/ingredient name	Test		Experiment		Result	
Proprietary	OECD 471		Experiment: In		Neg	gative
			Subject: Bacte			
	OECD 475		Experiment: In Subject: Mamr			gative
Carcinogenicity						
	Pocult		Chasica		Doso	Evnosuro
Product/ingredient name	Result		Species		Dose	Exposure
Not available.						
Product/ingredient name						
Not available.						
Not available.  Reproductive toxicity						

WCI A181 - Corrosion Inhibitor Page: 11/19

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
Proprietary	-	-	Positive	Rat	Oral	-
<u>Teratogenicity</u>						
Product/ingredient name Not available.	Result		Species	Dose		Exposure
Specific target organ toxici	ty (single ex	posure)				
Name			Category	Route o		Target organs
Methanol			Category 1 Category 3	Oral Not applic		ptic nerve arcotic effects
Specific target organ toxici	ty (repeated	exposure)				
Name			Category	Route o	•	Target organs
Proprietary			Category 1	Not deterr	nined th	yroid
Aspiration hazard						
Name				Result		
Not available.						

Information on the likely ToxKinetics - routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation.

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness.

**Skin contact**: Causes skin irritation.

**Ingestion**: Harmful if swallowed. Can cause central nervous system (CNS) depression.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

**Inhalation** : Adverse symptoms may include the following:

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations WCI A181 - Corrosion Inhibitor Page: 12/19

## Section 11. Toxicological information

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

**General** : Causes damage to organs through prolonged or repeated exposure.

Carcinogenicity : No known significant effects or critical hazards.Mutagenicity : No known significant effects or critical hazards.

**Teratogenicity**: May damage the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

### **Numerical measures of toxicity**

### **Acute toxicity estimates**

Route	ATE value
Oral	967.8 mg/kg
Dermal	3296.2 mg/kg
Inhalation (vapors)	38.69 mg/l

## Section 12. Ecological information

### **Toxicity**

WCI A181 - Corrosion Inhibitor Page: 13/19

Section 12. Ecological information					
Product/ingredient name	Result	Species	Exposure		
Methanol	Acute EC50 16.912 mg/l Marine water	Algae - Ulva pertusa	96 hours		
	Acute LC50 2500000 μg/l Marine water	Crustaceans - Crangon crangon - Adult	48 hours		
	Acute LC50 3289 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours		
	Acute LC50 100 mg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours		
	Chronic NOEC 9.96 mg/l Marine water	Algae - Ulva pertusa	96 hours		
Proprietary	Acute EC50 6600000 µg/l Fresh water	Algae - Chlorella pyrenoidosa	96 hours		
Торпскагу	Acute EC50 23 ppm Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours		
	Acute LC50 26400 µg/l Fresh water	Daphnia - Daphnia magna	48 hours		
	Acute LC50 502 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours		
Proprietary	Acute EC50 110 μg/l Fresh water	Algae - Chlorella pyrenoidosa - Exponential growth phase	72 hours		
	Acute EC50 14.22 ppb Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours		
	Acute EC50 18 ppb Fresh water	Daphnia - Daphnia magna	48 hours		
	Acute LC50 39 μg/l Marine water	Crustaceans - Americamysis bahia - Juvenile (Fledgling, Hatchling, Weanling)	48 hours		
	Acute LC50 0.01 µg/l Fresh water	Fish - Acipenser transmontanus - Larvae	96 hours		
	Chronic NOEC 25 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours		
	Chronic NOEC 125 µg/l Fresh water	Daphnia - Daphnia magna	21 days		

**Conclusion/Summary** 

: Not available.

### Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Proprietary	OECD 303a	91 % - 70 days	-	-
	OECD 301B	72 % - Readily - 28 days	10 mg/l	-
Product/ingredient name	Aquatic half-life	Photolysis		Biodegradability
Proprietary	-	-		Readily

Bioaccumulative potential			
Product/ingredient name	LogPow	BCF	Potential
Methanol	-0.77	<10	low
Proprietary	-0.67	1.82	low

### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Date of issue/Date of revision	3/29/2018	People + Products ⇒ Performance <sup>™</sup>	Version : 1.04	

WCI A181 - Corrosion Inhibitor Page: 14/19

## Section 12. Ecological information

Other adverse effects

: No known significant effects or critical hazards.

### Section 13. Disposal considerations

### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS#	Status	Reference number
Proprietary	96-45-7	Listed	U116
Methanol (I): Methyl alcohol (I)	67-56-1	Listed	U154

## Section 14. Transport information

DOT Classification PG\* : Packing group

UN1993	FLAMMABLE LIQUID, N.O.S. (methanol) RQ (methanol)	3	III
--------	---	---	-----

Additional information

### **Emergency Response Guide (ERG): 128**

### Reportable quantity

213.21 lbs / 96.796 kg [27.203 gal / 102.97 L]

Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

### Label



WCI A181 - Corrosion Inhibitor Page: 15/19

## Section 14. Transport information

**TDG** 

Classification

UN1993 FLAMMABLE LIQUID, N.O.S. (methanol)

III

3

Additional information

Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2. 18-2.19 (Class 3).

Label



### **IMDG Class**

UN1993 FLAMMABLE LIQUID, N.O.S. (methanol)

Not available.

III

3

Marine pollutant notes:

**Additional information** 

-

Label



### **IATA-DGR Class**

UN1993 FLAMMABLE LIQUID, N.O.S. (methanol)

Ш

Additional information

Label



WCI A181 - Corrosion Inhibitor Page: 16/19

## Section 15. Regulatory information

**U.S. Federal regulations** : TSCA 4(a) proposed test rules: Proprietary

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

All components are listed or exempted.

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)**  : Listed

**Clean Air Act Section 602** 

**Class I Substances** 

: Not listed

**Clean Air Act Section 602** 

**Class II Substances** 

: Not listed

**DEA List I Chemicals** 

: Not listed

(Precursor Chemicals)

**DEA List II Chemicals** (Essential Chemicals) : Not listed

**SARA 302/304** 

**Composition/information on ingredients** 

No products were found.

**SARA 304 RQ** : Not applicable.

**SARA 311/312** 

Classification : Fire hazard

> Immediate (acute) health hazard Delayed (chronic) health hazard

### Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	(acute) health	Delayed (chronic) health hazard
Methanol	10 - 30	Yes.	No.	No.	Yes.	Yes.
Proprietary	1 - 5	No.	No.	No.	Yes.	No.
Proprietary	1 - 5	No.	No.	No.	Yes.	No.

### **SARA 313**

	Product name	CAS number	%
Form R - Reporting requirements	methanol	67-56-1	10 - 30
	Proprietary	-	Proprietary
Supplier notification	methanol	67-56-1	10 - 30
	Proprietary	-	Proprietary

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

**State regulations** 

**Massachusetts** The following components are listed: Proprietary; METHANOL **New York** The following components are listed: Proprietary; Methanol

**New Jersey** The following components are listed: Proprietary; METHYL ALCOHOL; METHANOL

**Pennsylvania** The following components are listed: Proprietary; METHANOL WCI A181 - Corrosion Inhibitor Page: 17/19

## Section 15. Regulatory information

### California Prop. 65

**WARNING:** This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant	risk level Maximum acceptable dosage level
methanol	No.	Yes.	No.	23000 µg/day (ingestion) 47000 µg/day
Proprietary	Yes.	Yes.	Yes.	(inhalation) No.

### International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

**Canadian lists** 

Canadian NPRI : The following components are listed: Ethylene thiourea; Methanol

(Pollution Release)

CEPA Toxic substances : None of the components are listed.

Canada inventory-DSL / NDSL : All components are listed or exempted.

International lists
National inventory

Australia : Not determined.

Canada : All components are listed or exempted.
China : All components are listed or exempted.
Europe : All components are listed or exempted.
Japan : Japan inventory (ENCS): Not determined.

Japan inventory (ISHL): Not determined.

Malaysia : Not determined.

**New Zealand** : All components are listed or exempted.

Philippines : Not determined.

Republic of Korea : All components are listed or exempted. Taiwan : All components are listed or exempted.

WCI A181 - Corrosion Inhibitor Page: 18/19

### **Section 16. Other information**

### **National Fire Protection Association (U.S.A.)**



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Normal Package Size(s): Ball: 2" Ball 50/Cooler; 4" Ball 12/Cooler

Dry Product: 50 Lbs/Box

Liquid: 5 Gallon/55 Gallon/Bulk Pellets: 30 Lbs/Cooler; 24 Lbs/Pail Stix: 1 1/4": 50 Fach/Cooler

**History** 

Date of issue/Date of revision : 3/29/2018

Version : 1.04

Date of previous issue : 6/27/2017

Previous Validation Date : 6/27/2017

Prepared by : Jacam Regulatory Department

SDS Requests: : SDS@jacam.com

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References : Not available.

Indicates information that has changed from previously issued version.

**Notice to reader** 

WCI A181 - Corrosion Inhibitor Page: 19/19

### Section 16. Other information

This Safety Data Sheet ("SDS") is a mandatory disclosure pursuant to 29 CFR § 1910.1200 and related rules and regulations. Therefore, it is not intended, nor shall it serve to create, any rights, obligations, liabilities, and remedies, of any kind whatsoever, between Jacam Chemicals 2013, LLC and related entities ("Jacam") and any users of this SDS ("Users").

To the extent that a court of competent jurisdiction determines that this SDS creates any rights, obligations, liabilities, and remedies, of any kind whatsoever, notwithstanding the foregoing paragraph, Users accept the product AS IS and WITH ALL FAULTS. Further, Jacam DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Users' sole and exclusive remedies shall be (if any), in Jacam's sole and absolute discretion, either: (1) return of the product and repayment of the purchase price; or (2) repair/replacement of the product. In no event shall Jacam be liable for any damages of any kind whatsoever, including but not limited to, actual, compensatory, reliance, expectancy, foreseeable, future, statutory, incidental, consequential, and exemplary damages. Users assume any and all risks of any kind whatsoever that in any way relate to the product.

\*\*\* END OF SDS \*\*\*

3/29/2018