

Section: 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : PARA11089A

Other means of identification : Not applicable.

Recommended use : PARAFFIN DISPERSANT, Asphaltene Dispersant, SURFACTANT

Restrictions on use : Refer to available product literature or ask your local Sales Representative for restrictions on use and dose limits.

Company : ChampionX LLC
 11177 S. Stadium Drive
 Sugar Land, Texas 77478
 USA
 TEL: (281) 632-6500

Emergency telephone number : (800) 424-9300 (24 Hours) CHEMTREC

Issuing date : 07/11/2023

Section: 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2

Acute toxicity (Oral) : Category 4

Skin irritation : Category 2

Serious eye damage : Category 1

Germ cell mutagenicity : Category 1B

Carcinogenicity : Category 1B

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central Nervous System)

Specific target organ toxicity - repeated exposure : Category 2 (Nervous system)

Aspiration hazard : Category 1

GHS Label element

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : Highly flammable liquid and vapour.
 Harmful if swallowed.
 May be fatal if swallowed and enters airways.
 Causes skin irritation.
 Causes serious eye damage.
 May cause respiratory irritation.
 May cause drowsiness or dizziness.

SAFETY DATA SHEET

PARA11089A

May cause genetic defects.
May cause cancer.
Suspected of damaging fertility or the unborn child.
May cause damage to organs (Nervous system) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/ physician. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
Storage:
Store in a well-ventilated place.
Disposal:
Dispose of contents/ container to an approved waste disposal plant.

Other hazards : None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Concentration: (%)</u>
Toluene	108-88-3	30 - 60
Light Aliphatic Naphtha	64742-89-8	30 - 60
Organic Acid Salt	Proprietary	5 - 10
Light Aromatic Naphtha	64742-95-6	5 - 10
1,2,4-Trimethylbenzene	95-63-6	1 - 5
Isopropanol	67-63-0	1 - 5
Cumene	98-82-8	0.1 - 1

Section: 4. FIRST AID MEASURES

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Get medical attention if irritation develops and persists.

If swallowed : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Aspiration hazard if swallowed - can enter lungs and cause damage. Get medical attention immediately.

SAFETY DATA SHEET

PARA11089A

- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.
- Protection of first-aiders : In event of emergency assess the danger before taking action. Do not put yourself at risk of injury. If in doubt, contact emergency responders. Use personal protective equipment as required.
- Notes to physician : Treat symptomatically.
- Most important symptoms and effects, both acute and delayed : See Section 11 for more detailed information on health effects and symptoms.

Section: 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Foam
Carbon dioxide
Dry powder
Other extinguishing agent suitable for Class B fires
For large fires, use water spray or fog, thoroughly drenching the burning material.
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Fire Hazard
Keep away from heat and sources of ignition.
Flash back possible over considerable distance.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Hazardous combustion products : Decomposition products may include the following materials: Carbon oxides nitrogen oxides (NOx) Sulphur oxides
- Special protective equipment for firefighters : Use personal protective equipment.
- Specific extinguishing methods : Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
- Methods and materials for containment and cleaning up : Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise

SAFETY DATA SHEET

PARA11089A

contain material to ensure runoff does not reach a waterway. Do not flush into surface water or sanitary sewer system.

Section: 7. HANDLING AND STORAGE

- Advice on safe handling : Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Ground and bond container and receiving equipment. Open drum carefully as content may be under pressure. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not ingest. Wash face, hands and any exposed skin thoroughly after handling. Empty product containers may contain product residue. Do not pressurize, cut, heat, weld, or expose containers to flame or other sources of ignition.
- Conditions for safe storage : Keep away from heat and sources of ignition. Keep in a cool, well-ventilated place. Keep away from oxidizing agents. Keep container tightly closed. Store in suitable labelled containers.
- Suitable material : Keep in properly labelled containers.
- Unsuitable material : not determined

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m ³	NIOSH REL
		STEL	150 ppm 560 mg/m ³	NIOSH REL
		TWA	200 ppm	OSHA/Z2
		CEIL	300 ppm	OSHA/Z2
		Peak	500 ppm	OSHA/Z2
Light Aliphatic Naphtha	64742-89-8	TWA	500 ppm 2,000 mg/m ³	OSHA Z1
Light Aromatic Naphtha	64742-95-6	TWA	500 ppm 2,000 mg/m ³	OSHA Z1
		TWA	200 mg/m ³ (as total hydrocarbon vapor)	ACGIH
1,2,4-Trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m ³	NIOSH REL
		TWA	25 ppm	ACGIH
Isopropanol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m ³	NIOSH REL
		STEL	500 ppm 1,225 mg/m ³	NIOSH REL

SAFETY DATA SHEET

PARA11089A

		TWA	400 ppm 980 mg/m3	OSHA Z1
Cumene	98-82-8	TWA	5 ppm	ACGIH
		TWA	50 ppm 245 mg/m3	NIOSH REL
		TWA	50 ppm 245 mg/m3	OSHA Z1

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Eye protection : Safety goggles
Face-shield

Hand protection : Wear impervious chemical-resistant gloves when handling this product. The following glove types are recommended based on our review of glove manufacturer information and/or other available sources.
Nitrile rubber
Viton® gloves
Other glove types may be used for short term, incidental contact if determined by testing to provide adequate worker protection.
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection : Wear suitable protective clothing.

Respiratory protection : Use local exhaust ventilation or other engineering controls as necessary to control airborne vapour and mist.
Where concentrations in air may exceed the limits given in this section or when significant vapours are generated, use an approved air purifying respirator fitted with a gas and vapour cartridge.
Use a particulate pre-filter where operations generate significant mists or aerosols.
Recommended gas and vapour cartridge:
Organic vapour cartridge.
In event of emergency or planned entry into unknown concentrations a positive pressure, full-facepiece SCBA or supplied-air respirator should be used.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

The Personal Protective Equipment (PPE) recommendations provided above have been made in good faith based on typical expected conditions of use. PPE selection should always be completed in conjunction with a proper risk assessment and in accordance with a PPE management program.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
Colour : amber

SAFETY DATA SHEET

PARA11089A

Odour	: hydrocarbon-like
Flash point	: -3.9 °C, Method: Tag closed cup
pH	: Not applicable.
Odour Threshold	: no data available
Melting point/freezing point	: Pour point: -40 °C
Initial boiling point and boiling range	: 89.4 - 142.8 °C
Evaporation rate	: no data available
Flammability (solid, gas)	: Not applicable.
Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Relative vapour density	: no data available
Relative density	: 0.8200 - 0.8600, (15.6 °C),
Density	: 0.8167 - 0.8565 g/cm ³
Water solubility	: insoluble
Solubility in other solvents	: no data available
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: no data available
Thermal decomposition	: no data available
Viscosity, dynamic	: 2 - 8 mPa.s (23.9 °C)
Viscosity, kinematic	: 3.9 mm ² /s (40 °C)
Molecular weight	: no data available
VOC	: no data available

Note: properties listed in this section may be typical, calculated, or estimated values and should not be used as product specifications or for system design. For product specifications see the COA or Technical Data sheet.

Section: 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition	: Decomposition products may include the following materials:

SAFETY DATA SHEET

PARA11089A

on OSHA's list of regulated carcinogens.

NTP **Reasonably anticipated to be a human carcinogen**
Cumene 98-82-8

Reproductive effects : no data available
Germ cell mutagenicity : no data available
Teratogenicity : no data available
STOT - single exposure : no data available
STOT - repeated exposure : no data available
Aspiration toxicity : no data available

Section: 12. ECOLOGICAL INFORMATION

Toxicity

Environmental Effects : Toxic to aquatic life.
Harmful to aquatic life with long lasting effects.

Product

Toxicity to fish : LC50 Pimephales promelas (fathead minnow): 8.57 mg/l
Exposure time: 96 h
Test substance: Product
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC50 Daphnia magna (Water flea): 8.08 mg/l
Exposure time: 48 h
Test substance: Product
Test Type: static test

Components

Toxicity to algae : Toluene
EC50 Chlorella vulgaris (Fresh water algae): 134 mg/l
Exposure time: 72 h

Cumene
EC50 : 3.4 mg/l
Exposure time: 72 h

Components

Toxicity to bacteria : Toluene
84 mg/l
EC50 Nitrosomonas Sp.: 84 mg/l
Exposure time: 24 h

Isopropanol
1,050 mg/l

Components

Toxicity to fish (Chronic) : Toluene

SAFETY DATA SHEET

PARA11089A

toxicity) NOEC: 1.39 mg/l
Exposure time: 40 d
Species: Oncorhynchus kisutch (coho salmon)

Components

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Toluene
NOEC: 0.74 mg/l
Exposure time: 7 d
Species: Ceriodaphnia dubia

Persistence and degradability

no data available

Mobility

no data available

Bioaccumulative potential

no data available

Other information

no data available

Section: 13. DISPOSAL CONSIDERATIONS

The information presented only applies to the material as supplied. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated at the time of disposal to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Disposal methods : The product should not be allowed to enter drains, water courses or the soil. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

The presence of an RQ component (Reportable Quantity for U.S. DOT) in this product causes it to be regulated with an additional description of RQ for road, or as Environmentally hazardous for road and air, ONLY when the net weight in the package exceeds the calculated RQ for the product.

Land transport (DOT)

Proper shipping name : FLAMMABLE LIQUID, N.O.S.
Technical name(s) : Toluene, Light Aliphatic Naphtha

SAFETY DATA SHEET

PARA11089A

UN/ID No. : UN 1993
Transport hazard class(es) : 3
Packing group : II
Reportable Quantity (per package) : 2,269 lbs
RQ Component : Toluene

Air transport (IATA)

Proper shipping name : FLAMMABLE LIQUID, N.O.S.
Technical name(s) : Toluene, Light Aliphatic Naphtha
UN/ID No. : UN 1993
Transport hazard class(es) : 3
Packing group : II
Reportable Quantity (per package) : 2,269 lbs
RQ Component : Toluene

Sea transport (IMDG/IMO)

Proper shipping name : FLAMMABLE LIQUID, N.O.S.
Technical name(s) : Toluene, Light Aliphatic Naphtha
UN/ID No. : UN 1993
Transport hazard class(es) : 3
Packing group : II

Section: 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.
No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Toluene	108-88-3	1000	2669

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Acute toxicity (any route of exposure)
Germ cell mutagenicity
Carcinogenicity
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard
Skin corrosion or irritation
Serious eye damage or eye irritation

SAFETY DATA SHEET

PARA11089A

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

<u>Components</u>	<u>CAS-No.</u>	<u>Weight percent</u>
Toluene	108-88-3	30 - 60 %
1,2,4-Trimethylbenzene	95-63-6	1 - 5 %
Cumene	98-82-8	0.1 - 1 %

California Prop. 65

 **WARNING:** Cancer - www.P65Warnings.ca.gov

Cumene 98-82-8

 **WARNING:** Reproductive Harm - www.P65Warnings.ca.gov

Toluene 108-88-3

INTERNATIONAL CHEMICAL CONTROL LAWS :

United States TSCA Inventory

On TSCA Inventory

Canadian Domestic Substances List (DSL)

This product contains one or several components listed in the Canadian NDSL.

Australia. Australian Industrial Chemicals Introduction Scheme (AICIS)

not determined

Australian Inventory of Industrial Chemicals

not determined

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand

Not in compliance with the inventory

China Inventory of Existing Chemical Substances

On the inventory, or in compliance with the inventory

Japan. ENCS - Existing and New Chemical Substances Inventory

not determined

Korea. Korean Existing Chemicals Inventory (KECI)

not determined

Philippines Inventory of Chemicals and Chemical Substances (PICCS)

not determined

Taiwan Chemical Substance Inventory


not determined

Section: 16. OTHER INFORMATION

SAFETY DATA SHEET

PARA11089A

NFPA:



0 = not significant
1 = Slight
2 = Moderate
3 = High
4 = Extreme

Revision Date : 07/11/2023
Version Number : 1.5
Prepared By : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.